

DECLARATION OF PERFORMANCE

N.º 001DDPGP

1. Unique identification code of the product type: Dry-pressed ceramic tiles, with water absorption under 0.5% ($E_b \leq 0.5\%$), UGL or GL
2. Intended uses: For internal and external walls and floorings
3. Name and contact address of the manufacturer: Pavigrés Cerâmicas, S.A., Almas das Domingas, 3781-909 Anadia, Portugal
4. System of assessment and verification of constancy of performance: System 4
5. Declared performances

Essential characteristics	Performance	Harmonised standard
Reaction to fire	A1 / A1FL	EN 14411:2006
Release of dangerous substances, for (1): - Cadmium (Cd) - Lead (Pb)	NPD	
Breaking strenght (S)	$\geq 1500\text{ N}$	
Slipperiness (2)	NPD	
Durability: - Internal use: - Freeze-thaw resistance:	Pass	
Tactility (3)	NPD	
Bond strenght / adhesion	NPD	
Thermal shock resistance	Pass	

(1) Only for uses subject to regulation requirements on dangerous substances, i.e. whwn glazed ceramic tiles are used on surfaces in contact with food; to assess case by case.

(2) For floorings on pedestrian circulation áreas (where required by regulation).

(3) For tactile paving surfaces only, i.e. when required for blind or vision impaired persons.


NPD – No performance declared

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

The Administrator



(Jose Diogo)

Anadia, 17/06/2013