








## DECLARATION OF PERFORMANCE CPR 305/2011

MOSAICO DI VETRO · GLASS MOSAIC · MOSAÏQUE DE VERRE  
GLASMOSAİK · MOSAICO DE VIDRIO · СТЕКЛЯННАЯ МОЗАИКА

CARATTERISTICHE TECNICHE · TECHNICAL SPECIFICATIONS · CARACTÉRISTIQUES TECHNIQUES  
TECHNISCHE EIGENSCHAFTEN · CARACTERÍSTICAS TÉCNICAS · ТЕХНИЧЕСКИЙ РАЗДЕЛ

 <p>UNI EN ISO 10545 (13)</p> <p>RESISTENZA AGLI AGENTI CHIMICI RESISTANCE TO CHEMICAL AGENTS RESISTANCE AUX PRODUITS CHIMIQUES SÄURE- UND LAUGENBESTÄNDIGKEIT RESISTENCIA A LOS AGENTES QUÍMICOS УСТОЙЧИВОСТЬ К ВОЗДЕЙСТВИЮ КИСЛОТ</p> <p>resistente resistant résistant beständig resistente устойчива</p>	 <p>UNI EN ISO 10545 (12)</p> <p>RESISTENZA AL GELO FROST RESISTANCE RESISTANCE AU GEL FROSTBESTÄNDIGKEIT RESISTENCIA AL HIELO МОРОЗООУСТОЙЧИВОСТЬ</p> <p>resistente resistant résistant beständig resistente устойчива</p>																
 <p>UNI EN ISO 10545 (9)</p> <p>RESISTENZA AGLI SBALZI TERMICI RESISTANCE TO THERMAL SHOCKS RESISTANCE AUX CHOCS THERMIQUES TEMPERATURWECHSELBESTÄNDIGKEIT RESISTENCIA A LOS CAMBIOS DE TEMPERATURA УСТОЙЧИВОСТЬ К ПЕРЕПАДАМ ТЕМПЕРАТУРЫ</p> <p>resistente resistant résistant beständig resistente устойчива</p>	 <p>DIN 51097</p> <p>RESISTENZA ALLA SCIVOLOSITÀ A PIEDI NUDI SLIP RESISTANCE ON BARE FEET RESISTANCE AU GLISSEMENT A PIEDS NUS RUTSCHFESTIGKEIT BARFUSS RESISTENCIA ANTIDESLIZANTE CON PIES DESNUDOS УСТОЙЧИВОСТЬ К СКОЛЬЖЕНИЮ, БОСИКОМ</p> <p>classe B class B classe B Klasse B clase B класс B</p>																
 <p>UNI EN ISO 10545 (3)</p> <p>ASSORBIMENTO ACQUA WATER ABSORPTION ABSORPTION D'EAU WASSERAUFNAHME ABSORCION DE AGUA ВОДОПОГЛОЩЕНИЕ</p> <p>nullo none nulle null nula ноль</p>	 <p>DIN 51130</p> <p>RESISTENZA ALLA SCIVOLOSITÀ A PIEDI CALZATI SLIP RESISTANCE WITH SHOES RESISTANCE AU GLISSEMENT A PIEDS CHAUSSÉS RUTSCHFESTIGKEIT MIT SCHUHEN RESISTENCIA ANTIDESLIZANTE CON PIES CALZADOS УСТОЙЧИВОСТЬ К СКОЛЬЖЕНИЮ, В ОБУВИ</p> <p>R9</p>																
 <p>DIN 51094</p> <p>RESISTENZA DEI COLORI ALLA LUCE COLOURS RESISTANCE TO FADING RESISTANCE DES COULEURS A LA LUMIERE FARBBESTÄNDIGKEIT RESISTENCIA DE LOS COLORES A LA LUZ УСТОЙЧИВОСТЬ К СВЕТУ</p> <p>resistente resistant résistant beständig resistente устойчива</p>	<h3>TEST ASTM</h3> <table border="1"> <thead> <tr> <th>TEST PERFORMED AND REQUIREMENTS</th> <th>CONCLUSIONS</th> </tr> </thead> <tbody> <tr> <td>Range of thickness (ASTM C499)</td> <td>passes</td> </tr> <tr> <td>Facial dimensions (ASTM C499)</td> <td>passes</td> </tr> <tr> <td>Wedging (ASTM C502)</td> <td>passes</td> </tr> <tr> <td>Water absorption (ASTM C373)</td> <td>passes</td> </tr> <tr> <td>Thermal shocks (ASTM C484)</td> <td>passes</td> </tr> <tr> <td>Bond Strength (ASTM C482)</td> <td>passes</td> </tr> <tr> <td>Crazing (ASTM C424)</td> <td>passes</td> </tr> </tbody> </table>	TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS	Range of thickness (ASTM C499)	passes	Facial dimensions (ASTM C499)	passes	Wedging (ASTM C502)	passes	Water absorption (ASTM C373)	passes	Thermal shocks (ASTM C484)	passes	Bond Strength (ASTM C482)	passes	Crazing (ASTM C424)	passes
TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS																
Range of thickness (ASTM C499)	passes																
Facial dimensions (ASTM C499)	passes																
Wedging (ASTM C502)	passes																
Water absorption (ASTM C373)	passes																
Thermal shocks (ASTM C484)	passes																
Bond Strength (ASTM C482)	passes																
Crazing (ASTM C424)	passes																

Institutions that have provided datas are: Università di Trento, Centro Ceramico di Bologna, Main Laboratory Sassuolo, CSI.

### TREND GROUP S.p.A.

Head office: Piazzale Fraccon, 8 · 36100 VICENZA · Italy · Phone +39 0444 338711 · Fax +39 0444 338747 · Commercial office: Fax +39 0444 338777  
Administrative office: Fax +39 0444 338757 · info@trend-vi.com · www.trend-vi.com · Posta Elettronica Certificata (PEC): trendgroup@legalmail.it  
C.F. / R.I. Vicenza 02780620247 · Part. I.v.a.: IT 02780620247 · R.E.A. n. 274358 · Capitale Sociale € 1.560.000,00 i.v.  
Production site: Via San Marco, 17 (Z.I.) · 33099 Vivaro (PN) · Phone +39 0427 976111 · Fax +39 0427 976120

