

DECLARATION OF PERFORMANCE

001-DPR-20130701

1. **Unique identification code of the product-type:**
Dry pressed ceramic tiles with low water absorption $E \leq 0.5\%$
2. **Intended uses:**
Internal and external walls and floorings.
3. **Manufacturer:**
PORCELANOSA S.A.
Ctra. N-340 Km. 56,2
12540 Vila-real (Castellón)
SPAIN
4. **System(s) of assessment and verification of constancy of performance (AVCP)**
System 4
5. **Notified laboratory:**
Not applicable
6. **Declared performance**

Characteristics	Performance	Harmonised technical specification
Reaction to fire:	A1-A1 _{fl}	EN 14411 : 2012
Release of dangerous substance		
Cadmium	NPD	
Lead	NPD	
Breaking strength	≥ 1300 N	
Slip resistance (Pendulum method (wet), slider 57), CEN/TS 16165:2012)	NPD	
Tactility	NPD	
Bond strength/Adhesion		
Cementitious adhesive, type C2	1,5 N/mm ²	
Reactive resin adhesive	3,1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
Internal use	Pass	
External use (Freeze-thaw resistance)	Pass	

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Name and function: Manuel Diago García (proxy)

Place and date of issue: Vila-real July 1, 2013

Signature

