

DECLARATION OF PERFORMANCE

003-DPR-20130701

1. **Unique identification code of the product-type:**
Dry pressed ceramic tiles with water absorption E > 10%
2. **Intended uses:**
Internal walls.
3. **Manufacturer:**
PORCELANOSA S.A.
Ctra. N-340 Km. 56,2
12540 Vila-real (Castellón)
SPAIN
4. **System(s) of assessment and verification of constancy of performance (AVCP)**
System 4
5. **Notified laboratory:**
Not applicable
6. **Declared performance**

Characteristics	Performance	Harmonised technical specification
Reaction to fire:	A1	EN 14411 : 2012
Release of dangerous substance		
Cadmium	NPD	
Lead	NPD	
Breaking strength	≥600 N	
Bond strength/Adhesion		
Cementitious adhesive, type C1	0,6 N/mm ²	
Cementitious adhesive, type C2	1,9 N/mm ²	
Dispersion adhesive, D1	2 N/mm ²	
Dispersion adhesive, D2	2,6 N/mm ²	
Reactive resin adhesive	6,9 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
Internal use	Pass	

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Name and function: Manuel Diago García (proxy)

Place and date of issue: Vila-real July 1, 2013

Signature

